

Q.brixx A106

Measurement Module for Strain Gage and LVDT/RVDT



Q.brixx brings the performance and functionality of Q.bloxx into a scalable, portable, and rugged form factor. Q.brixx DAQ systems can consist of up to 16 measurement modules and an integrated, high-performance controller for communication, control, and data logging purposes. With a robust aluminum housing capable of withstanding severe shock and vibration, Q.brixx is ideal for on-the-go applications in potentially harsh environments.

- Electromagnetic compatibility according EN 61000-4 and EN 55011
- Robust and reliable stable and compact aluminum housing, easy to carry
- Power supply 10 ... 30 VDC
- Temperature range -20 up to +60°C
- High density and flexibility up to 16 modules in one system in any constellation




Key Features

- 2 galvanically isolated analog inputs channels
strain gage and inductive half and full bridges, LVDT, RVDT quarter bridge with completion terminal
- DC and carrier frequency (CF) principle
2.5 and 5 VDC excitation, 2.5 and 5 VDCeff excitation carrier frequency, 600 Hz or 4.8 kHz configurable per channel
- 2 Analog output channels
±10 VDC, 10 kHz update rate per channel
- High-accuracy digitization
24-bit ADC, 10 kHz sample rate per channel
- 4 digital I/Os
input: state, tare, memory reset, output: state, alarm, threshold
- Signal conditioning
linearization, filtering, average, scaling, min/max, RMS, arithmetic, alarm
- 3-Way galvanic isolation
500 VDC channel to channel, channel to power supply, and channel to bus



Block diagram



Technical Data

Analog Input

Channels	2
Accuracy	0.02 % typical 0.05 % in controlled environment ¹ 0.1 % in industrial area ²
Linearity error	0.02 % typical full-scale
Repeatability	0.01 % typical (within 24 hrs)
Input impedance	>10 MΩ
Isolation voltage	500 VDC channel to channel, to power supply, channel to bus ³

¹ according to EN 61326 2006: appendix B

² according to EN 61326 2006: appendix A

³ noise pulses up to 1000 VDC, continuous up to 250 VDC

Analog to Digital Conversion

Resolution	24-bit
Sample rate	10 kHz per channel
Modulation method	sigma-delta
Anti-aliasing filter	2 kHz, 3rd order (DC excitation) 1 kHz, 3rd order (4.8 kHz CF excitation) 100 Hz, 3rd order (600 Hz CF excitation)
Digital filters	Infinite impulse response (IIR), low-pass, high-pass, band-pass, band-stop, to 8th order Butterworth or Bessel, frequency range 0.1 Hz to 1 kHz in steps of 0.1 (adjustable via software)
Averaging	configurable or automatic according to the user-defined data rate

Analog Output

Channels	2		
Accuracy	0.02 % typical		
Voltage output	±10 VDC		
Allowable load resistance	>2 kΩ		
Long-term drift	<1 mV / 24 hrs	<2.5 mV / 8000 hrs	
Temperature drift	<1 mV / 10 K Offset drift	<0.05 % / 10 K Gain drift	
Noise voltage	<2 mV at 10 Hz	<10 mV at 1 kHz	

Digital Input & Output

Channels	4 configurable I/Os		
Mode(s) of operation	status		
Logic voltage	<2 VDC (Low) >10 VDC (High)		
Input type	PNP (current sinking)		
Input voltage	30 VDC max.		
Output voltage	10 to 30 VDC (external supply required)		
Contact	open drain p-channel MOSFET		
Load capacity	30 VDC / 100 mA (ohmic load)		

Strain Gage Measurement

Bridge configuration(s)	resistive full-bridge (4/6-wire) resistive half-bridge (3/5-wire) resistive quarter-bridge 120 Ω or 350 Ω (3-wire, with bridge completion terminal)			
Allowable sensor cable length	<300 m (DC and 600 Hz CF excitation) <100 m ¹ (4.8 kHz CF excitation)			
Shunt resistor	100 kΩ internal resistor			
Bridge excitation	2.5 - 5 VDC 2.5 - 5 V _{eff} (Carrier Frequency)			
Bridge excitation stability	<0.01% / 24 hrs			
Bridge excitation drift	<0.02% / 10 K			
	5 VDC	5 V_{eff} (CF)	2.5 VDC	2.5 V_{eff} (CF)
Allowable sensor resistance	>300 Ω	>300 Ω	>100 Ω	>100 Ω
Input range	±1.25 mV/V	±1.25 mV/V	±2.5 mV/V	±2.5 mV/V
	±2.5 mV/V	±2.5 mV/V	±5 mV/V	±5 mV/V
	±25 mV/V	±25 mV/V	±50 mV/V	±50 mV/V
	±50 mV/V	±50 mV/V	±100 mV/V	±100 mV/V
	±100 mV/V	±100 mV/V	±200 mV/V	±200 mV/V
	±200 mV/V	±200 mV/V	±400 mV/V	±400 mV/V
	±500 mV/V	±500 mV/V	±1000 mV/V	±1000 mV/V
Long-term stability	<0.2 μV/V / 24 hrs (DC excitation) <0.1 μV/V / 24 hrs (CF excitation)		<2 μV/V / 8000 hrs (DC excitation) <1 μV/V / 8000 hrs (CF excitation)	
Temperature drift (range 2.5 mV/V)	<0.2 μV/V / 10 K Offset drift		<0.05 % / 10 K Gain drift	
Signal-to-noise ratio	<0.3 μV/V at 10 Hz		<1 μV/V at 100 Hz	

¹ low capacity sensor cable is strongly recommended

LVDT/RVDT Measurement

Sensor connection	4- / 6-wire	
Sensor excitation (selectable)	5 V_{eff}	2.5 V_{eff}
Allowable sensor resistance	>300 Ω	>100 Ω
Input range	±1.25 mV/V	±2.5 mV/V
	±2.5 mV/V	±5 mV/V
	±25 mV/V	±50 mV/V
	±50 mV/V	±100 mV/V
	±100 mV/V	±200 mV/V
	±200 mV/V	±400 mV/V
	±500 mV/V	±1000 mV/V
Allowable sensor cable length	<100 m ¹	
Long-term stability	<0.1 μV/V / 24 hrs	<1 μV/V / 8000 hrs
Temperature drift (range 2.5 mV/V)	<0.2 μV/V / 10 K Offset drift	<0.05 % / 10 K Gain drift
Signal-to-noise ratio	<0.3 μV/V at 10 Hz	<1 μV/V at 100 Hz

¹ low capacity sensor cable is strongly recommended

Digital to Analog Conversion

Resolution	16-bit
Update rate	10 kHz per channel
Settling time	3 μs

Communication Interface

Protocols	proprietary Localbus (115200 bps to 24 Mbps, latency <100 ns) ASCII (19200 bps to 115200 bps) Modbus RTU Profibus-DP (19200 bps to 12 Mbps) (special Firmware required)
Data format	8E1
Electrical standard	ANSI/TIA/EIA-485-A, 2-wire

Power Supply

Input voltage	10 to 30 VDC, overvoltage and overcurrent protection
Power consumption	2.5 W (approx.)
Input voltage influence	<0.001 % / V

Environmental Specifications

Electromagnetic compatibility (EMC)	according to IEC 61000-4 and EN 55011
Operating temperature	-20°C to +60°C
Storage temperature	-40°C to +85°C
Relative humidity	5 - 95 % at 50°C (non-condensing)

Q.brixx A106

Measurement Module for Strain Gage and LVDT/RVDT

Remarks

Validity of all listed specifications are subject to a warm-up period of at least 45 minutes

Specifications subject to change without notice

Mechanical information

Material	Aluminum
Measurements (W x H x D)	30 x 125 x 155 mm
Weight	approx. 200 g

Ordering Information

Article number	796640
Accessories	Terminal B4/120-A106, article number 894387
	Terminal B4/350-A106, article number 894488

Gantner Instruments

Austria | Germany | France | Sweden | India | USA | China | Singapore
Montafonerstraße 4 · A-6780 Schruns · T +43 55 56 · 77 463-0

office@gantner-instruments.com
www.gantner-instruments.com