


# Q.raxx XE A104 TCx

## Thermocouple Measurement Module


Q.raxx XE is an new addition to the Q.series product family - the ideal 19" rackmount EtherCAT DAQ solution for applications that require high channel density and custom sensor terminations. Q.raxx XE DAQ systems can consist of an integrated EtherCAT bus coupler for communication and 10 measurement modules capable of up to 100 kHz sampling per channel with short cycle times and low jitter for accurate synchronization

- According 19"-standard IEC
- Electromagnetic Compatibility according to EN61000-4 and EN55011
- High density and flexibility with 13 modules in one system in any constellation
- FoE ( file access over EtherCAT, ETG.1000.5) and CoE (CAN over EtherCAT, ETG.50001.1)



### Key Features


- 8 analog input channels  
thermocouple (type B / E / J / K / L / N / R / S / T / U), voltage ( $\pm 80$  mV)
- High-accuracy digitization  
24-bit ADC, 100 Hz sample rate per channel, 50/60 Hz mains rejection
- Automatic linearization correction  
optimal position of the interpolation points adjusted to the input range
- Open thermocouple detection  
detect broken wire, loose connection or thermocouple burnout
- 3-Way galvanic isolation  
100 VDC channel to channel, 500 VDC channel to power supply and bank
- Electromagnetic compatibility (EMC)  
according to IEC 61000-4 and EN 55011



# Q.raxx XE A104 TCx

## Thermocouple Measurement Module

### Block diagram



### Technical Data

#### Analog Input

Channels	8
Accuracy	0.01 % typical
	0.025 % in controlled environment <sup>1</sup>
	0.05 % in industrial area <sup>2</sup>
Linearity error	0.01 % typical full-scale
Repeatability	0.003 % typical (within 24 h)
Input impedance	>10 MΩ
Isolation voltage	500 VDC channels to power supply channel to bus <sup>3</sup>
	100 VDC continuous, channel to channel

<sup>1</sup> according to EN 61326 2006: appendix B

<sup>2</sup> according to EN 61326 2006: appendix A

<sup>3</sup> noise pulses up to 1000 VDC, continuous up to 250 VDC

#### Thermocouple Measurement

	Type	Range	Not adjusted, with CJC terminal
Deviation in the relevant Temperature range  The specifications are valid with enabled mains frequency rejection 50 Hz resp. 60 Hz	Type B	400°C to 1820°C	< ±2.5°C
	Type E, J, K	-100°C to 1000°C	< ±1.5°C
	Type E	-270°C to 1000°C	< ±1.5°C
	Type K	-270°C to 1372°C	< ±1.5°C
	Type L	-200°C to 900°C	< ±1.5°C
	Type N	-100°C to 1000°C	< ±1.5°C
	Type N	-270°C to 1300°C	< ±1.5°C
	Type R, S	-50°C to 1768°C	< ±1.5°C
	Type T, U	-100°C to 400°C	< ±1.5°C
	Type T	-270°C to 400°C	< ±1.5°C
Long-term drift	<0.025°C / 24 h		<0.05°C / 8000 h
Temperature influence	Offset drift		Gain drift
	<0.05°C / 10 K		<0.02% / 10 K
Uncertainty CJC	<0.3°C		

# Q.raxx XE A104 TCx

## Thermocouple Measurement Module

### Analog-to-Digital Conversion

Resolution	24-bit
Sample rate	100 Hz per channel fast mode 10 Hz per channel with 60 Hz mains frequency rejection 6 Hz per channel with 50 Hz mains frequency rejection
Modulation method	sigma-delta
Digital filters	Infinite impulse response (IIR), low-pass, Butterworth or Bessel (2nd, 4th, 6th or 8th order), frequency range 0.1 Hz to 10 Hz (adjustable via software)
Averaging	configurable or automatic according to the user-defined data rate

### Communication Interface EtherCAT

Electrical standard	RS-485, 2-wire
Protocols	EtherCAT (LVDS)

### Input Power

Input voltage	10 to 30 VDC, overvoltage and overcurrent protection
Power consumption	2 W (approx.)
Input voltage influence	<0.001 % / V

### Environmental Specifications

Operating temperature	-20°C to +60°C
Storage temperature	-40°C to +85°C
Relative humidity	5 - 95 % at 50°C (non-condensing)

### Remarks

Validity of all listed specifications are subject to a warm-up period of at least 45 minutes

Specifications subject to change without notice

### Mechanical information

Material	Aluminum
Measurements (W x H x D)	30x 128 x 120mm
Weight	approx. 200 g

### Ordering Information

Article number	644325
----------------	--------

### Gantner Instruments

Austria | Germany | France | Sweden | India | USA | China | Singapore  
Montafonerstraße 4 · A-6780 Schruns · T +43 55 56 · 77 463-0

office@gantner-instruments.com  
www.gantner-instruments.com