

# Q.raxx XE D105

## Digital Output Module


Q.raxx XE is an new addition to the Q.series product family - the ideal 19" rackmount EtherCAT DAQ solution for applications that require high channel density and custom sensor terminations. Q.raxx XE DAQ systems can consist of an integrated EtherCAT bus coupler for communication and 10 measurement modules capable of up to 100 kHz sampling per channel with short cycle times and low jitter for accurate synchronization

- According 19"-standard IEC
- Electromagnetic Compatibility according to EN61000-4 and EN55011
- High density and flexibility with 13 modules in one system in any constellation
- FoE ( file access over EtherCAT, ETG.1000.5) and CoE (CAN over EtherCAT, ETG.50001.1)



### Key Features

- 16 Digital outputs  
status, single bit or bitset
- Fast response time  
up to 10  $\mu$ s per channel
- High load capacity  
30 VDC / 500 mA, short circuit proof
- 3-Way galvanic isolation  
500 VDC group to group, group to power supply, and group to bus



# Q.raxx XE D105

## Digital Output Module

### Technical Data

#### Digital Output

Channels	16		
Mode(s) of operation	status		
Contact	open drain p-channel MOSFET		
Output voltage	12 to 30 VDC (external supply required)		
Load capacity	30 VDC / 500 mA (ohmic load)		
Response time	10 µs (>0.5 A)	100 µs (>0.1 A)	1000 µs (<0.1 A)
Isolation voltage	500 VDC, group to group, group to power supply, group to bus <sup>1</sup>		

<sup>1</sup> noise pulses up to 1000 VDC, continuous up to 250 VDC

#### Communication Interface EtherCAT

Electrical standard	RS-485, 2-wire
Protocols	EtherCAT (LVDS)

#### Input Power

Input voltage	10 to 30 VDC, overvoltage and overcurrent protection
Power consumption	2 W (approx.)
Input voltage influence	<0.001 % / V

#### Environmental Specifications

Electromagnetic compatibility (EMC)	according to IEC 61000-4 and EN 55011
Operating temperature	-20°C to +60°C
Storage temperature	-40°C to +85°C
Relative humidity	5 - 95 % at 50°C (non-condensing)

#### Remarks

Validity of all listed specifications are subject to a warm-up period of at least 45 minutes
Specifications subject to change without notice

#### Mechanical information

Material	Aluminum
Measurements (W x H x D)	30x 128 x 120mm
Weight	approx. 200 g

#### Ordering Information

Article number	533120
----------------	--------

#### Gantner Instruments

Austria | Germany | France | Sweden | India | USA | China | Singapore  
Montafonerstraße 4 · A-6780 Schruns · T +43 55 56 · 77 463-0

office@gantner-instruments.com  
www.gantner-instruments.com