

PT9420 (Extended Range)

Extended Ranges • 4...20mA, 0...20mA

Absolute Linear Position to 1700 inches (4300 cm)

Stroke Range Options: 0-600 to 0-1700 inches

VLS Option To Prevent Free-Release Damage

IP68 • NEMA 6 Protection • Hazardous Area Certification



GENERAL

Full Stroke Range Options (on this datasheet)	0-600 to 0-1700 inches
Output Signal Options	4...20 mA (2-wire) and 0...20 mA (3-wire)
Accuracy	± 0.12% full stroke
Repeatability	± 0.05% full stroke
Resolution	essentially infinite
Measuring Cable	nylon-coated stainless steel
Enclosure Material	powder-painted aluminum or 303 stainless steel
Sensor	plastic-hybrid precision potentiometer
Potentiometer Cycle Life	≥ 250,000, min.
Maximum Retraction Acceleration/ Velocity	see ordering information
Weight, Aluminum (Stainless Steel) Enclosure	14 lbs. (28 lbs.) max.

ELECTRICAL

Input Voltage	see ordering information
Input Current	20 mA max.
Maximum Loop Resistance (Load)	(loop supply voltage – 8)/0.020
Circuit Protection	38 mA max.
Impedance	100M ohms @ 100 VDC, min.
Output Signal, Zero Adjust	up to 50% of full stroke range
Output Signal, Span Adjust	to 50% of factory set span


ENVIRONMENTAL

Enclosure	NEMA 4/4X/6, IP 67/68
Hazardous Area Certification	see ordering information
Operating Temperature	-40° to 200°F (-40° to 90°C)
Vibration	up to 10 g to 2000 Hz maximum
Thermal Effects, Zero	0.01% f.s./°F, max.
Thermal Effects, Span	0.01%/°F, max.

EMC COMPLIANCE PER DIRECTIVE 89/336/EEC

Emission / Immunity	EN50081-2 / EN50082-2
---------------------	-----------------------


20630 Plummer Street • Chatsworth, CA 91311
tel: 800.423.5483 • +1.818.701.2750 • fax: +1.818.701.2799



The PT9420 is a great value for demanding long-range applications requiring a 4 - 20 mA linear position feedback signal. Sealed to meet NEMA 4 standards, this Cable-Extension Transducer will perform even under the harshest of environmental conditions.

As a member of Celesco's innovative family of NEMA-4 rated cable-extension transducers, the PT9420 offers numerous benefits. It installs in minutes, functions properly without perfectly parallel alignment, and when its cable is retracted, it measures only 6".

Output Signal:




*Optional 3-wire, 0...20mA output signal available.




celesco.com • info@celesco.com


Outline Drawing



mounting hole detail




eyelet detail



A DIMENSION

RANGE	inches [mm]
600	1.76 [44,7]
800	1.58 [40,1]
1000	1.98 [50,2]
1200	1.98 [50,2]
1500	1.86 [47,2]
1700	2.11 [53,6]



DIMENSIONS ARE IN INCHES [MM]
tolerances are 0.03 IN. [0.5 MM] unless otherwise noted.

* tolerance = +.005 -.001 [+ .13 -.03]
** tolerance = +.005 -.005 [+ .13 -.13]

VLS Option - Free Release Protection

The patented Celesco Velocity Limiting System (VLS) is an option for PT9000 Series cable extension transducers that limits cable retraction to a safe 40 to 55 inches per second for the single spring option and 40 to 80 inches per second for the higher tension dual spring option.

The VLS option prevents the measuring cable from ever reaching a damaging velocity during an accidental free release. This option is ideal for mobile applications that require frequent cable disconnection and reconnection. It prevents expensive unscheduled downtime due to accidental cable mishandling or attachment failure.

How To Configure Model Number for VLS Option:

VLS 9420 -

creating VLS model number (example)...

1. select PT9420 model
2. remove "PT" from the model number
3. add "VLS"
4. completed model number !

PT9420-1200-111-1110

~~PT~~ **9420-1200-111-1110**

VLS + 9420-1200-111-1110

VLS9420-1200-111-1110

Ordering Information:

Model Number:

PT9420- _____ **- 1** _____ **0**

order code: **R** **A** **B** **C** **D** **E** **F** **G**

Sample Model Number:

PT9420 - 1200 - 111 - 1110

R range: 1200 inches
A enclosure/cable tension: aluminum
B measuring cable: nylon-coated stainless front
C cable exit: 4...20 mA, 2-wire
D output signal: 6-pin plastic connector
E electrical connection:

Full Stroke Range:

R order code:	0600	0800	1000	1200	1500	1700
full stroke range, min:	600 in.	800 in.	1000 in.	1200 in.	1500 in.	1700 in.
cable tension (±35%):	27 oz.	24 oz.	20 oz.	19 oz.	18 oz.	17 oz.

Enclosure Material:





A order code:	1	3
enclosure material:	powder-painted aluminum	303 stainless steel
max. acceleration:	1g	1g
max. velocity:	60 inches/sec.	60 inches/sec.

Measuring Cable:







B order code:	1	2
cable construction:	nylon-coated stainless steel rope*	bare stainless steel rope*
general use:	indoor	outdoor, debris, high temperature

stroke range:	0600	0800	1000	1200	1500	1700
*cable diameter: nylon-coated stainless:	.034 in.	.019 in.	.019 in.	.019 in.	.014 in.	.014 in.
bare stainless:	.031 in.	.018 in.	.018 in.	.018 in.	.015 in.	.015 in.

Cable Exit:


C order code:	1	2	3	4
	front	top	back	down
				

Output Signals:

D order code:	1	2	3	4	5*	6*
output signal options:	4...20 mA 	20...4 mA 	0...20 mA 	20...0 mA 	4...20 mA 	20...4 mA 
sensitivity:	16 mA/full stroke ±0.25%		20 mA/full stroke ±0.25%		16 mA/full stroke ±0.25%	
wiring configuration:	2 - wire		3 - wire		2 - wire	
input voltage:	8 - 34 vdc		14 - 29 vdc		14 - 32 vdc	
hazardous area certification:			not certified		CSA • Cenelec	

Output Signal Example:

ordercode = **1** = 4...20 mA →



Hazardous Area Certifications:



CSA Standard 22.2
Class 1
Groups A, B, C and D











Cenelec
LCIE EEx
ia IIC T4

***IMPORTANT:** intrinsically safe when powered from a CSA certified zener barrier rated 28 VDC max, 110 mA max per installation drawing#677984


Ordering Information (cont.):

Electrical Connection:

1 order code: 6-pin plastic connector w/mating plug IP 67, NEMA 4X**, 6  1/2 - 5/16" [14 - 8 mm] cable dia. 16 AWG max conductor size connector: MS3102E-14S-6P mating plug: MS3106E-14S-6S	2 10-ft. [3 M] waterproof cable IP 67, NEMA 4X**, 6  10 ft. x 0.4-in. dia. [3 M x 10 mm dia.] 18 AWG, type SJTOW	3 6-pin metal connector w/mating plug IP 65, NEMA 4  3/8-in. [9 mm] max cable dia. 16 AWG max conductor size connector: MS3102E-14S-6P mating plug: MS3106E-14S-6S	4 25-ft. [7.5 M] instrumentation cable IP 67, NEMA 6  25 ft. x 0.2-in. dia. [7.5 M x 5 mm dia.] 24 AWG, shielded																																										
5 100-ft. [30 M] waterproof cable IP 67, NEMA 4X**, 6  100 ft. x 0.4-in. dia. [30 M x 10 mm dia.] 18 AWG, type SJTOW	6 10-ft. [3 M] pressure tested* waterproof cable IP 68, NEMA 4X**, 6P  10 ft. x 0.4-in. dia. [3 M x 10 mm dia.] 18 AWG, type SJTOW	7 100-ft. [30 M] pressure tested* waterproof cable IP 68, NEMA 4X**, 6P  100 ft. x 0.4-in. dia. [30 M x 10 mm dia.] 18 AWG, type SJTOW																																											
<table> <tr> <th colspan="3">6-pin Mating Plug</th> <th colspan="2">Waterproof Cable</th> <th colspan="2">Instrumentation Cable</th> </tr> <tr> <th>pin</th> <th>2-wire</th> <th>3-wire</th> <th>color code</th> <th>2-wire</th> <th>3-wire</th> <th>color code</th> </tr> <tr> <td>A</td> <td>8...34 vdc***</td> <td>14...29 vdc common</td> <td>WHITE</td> <td>8...34 vdc***</td> <td>14...29 vdc common</td> <td>RED</td> </tr> <tr> <td>B</td> <td>4...20 mA out</td> <td>0...20 mA out</td> <td>BLACK</td> <td>4...20 mA out</td> <td>0...20 mA out</td> <td>BLACK</td> </tr> <tr> <td>C</td> <td>-</td> <td>-</td> <td>GREEN</td> <td>case ground</td> <td>case ground</td> <td>WHITE</td> </tr> <tr> <td>D</td> <td>case ground</td> <td>-</td> <td></td> <td></td> <td></td> <td>GREEN</td> </tr> </table> <div>  <p>contact view</p> </div>				6-pin Mating Plug			Waterproof Cable		Instrumentation Cable		pin	2-wire	3-wire	color code	2-wire	3-wire	color code	A	8...34 vdc***	14...29 vdc common	WHITE	8...34 vdc***	14...29 vdc common	RED	B	4...20 mA out	0...20 mA out	BLACK	4...20 mA out	0...20 mA out	BLACK	C	-	-	GREEN	case ground	case ground	WHITE	D	case ground	-				GREEN
6-pin Mating Plug			Waterproof Cable		Instrumentation Cable																																								
pin	2-wire	3-wire	color code	2-wire	3-wire	color code																																							
A	8...34 vdc***	14...29 vdc common	WHITE	8...34 vdc***	14...29 vdc common	RED																																							
B	4...20 mA out	0...20 mA out	BLACK	4...20 mA out	0...20 mA out	BLACK																																							
C	-	-	GREEN	case ground	case ground	WHITE																																							
D	case ground	-				GREEN																																							


Notes: { * -Test pressure: 100 feet [30 meters] H₂O (40 PSID); Test Medium: Air; Duration: 2 hours.
 ** -NEMA 4X applies to stainless steel enclosure only.
 *** -14-32 VDC for hazardous area option.

Output Signal Settings:



The output signal direction can be reversed at any time by simply changing the dip-switch settings found on the internal signal board. After the settings have been changed, adjustment of the Zero and Span trimpots will be required to precisely match signal values to the beginning and end points of the stroke.

To gain access to the signal board, remove four Allen-Head Screws and remove end cover bracket.



Caution! Do Not Remove Spring-Side End Cover
 Removing spring-side end cover could cause spring to become unseated and permanently damaged.

version: 12.0 last updated: November 10, 2014